



Controlling Fluid-Induced Seismicity during a 6.1-km-Deep Geothermal Stimulation in Finland

Grzegorz Kwiatek^{1,2}, Tero Saarno³,

Thomas Ader⁴, Felix Bluemle¹, Marco Bohnhoff^{1,2}, Michael Chendorain⁴, Georg Dresen^{1,5}, Pekka Heikkinen^{3,6}, Ilmo Kukkonen⁶, Peter Leary⁷, Maria Leonhardt¹, Peter Malin⁷, Patricia Martínez-Garzón¹, Kevin Passmore⁷, Paul Passmore⁷, Sergio Valenzuela⁷, and Christopher Wollin¹


1. Helmholtz Centre Potsdam, GFZ German Research Centre for Geosciences, Potsdam Germany
2. Free University Berlin, Berlin, Germany
3. St1 Deep Heat Oy, Helsinki, Finland
4. Arup, London, United Kingdom
5. University of Potsdam, Potsdam, Germany
6. University of Helsinki, Helsinki, Finland
7. ASIR Advanced Seismic Instrumentation and Research, Dallas, United States

Introduction

- Seismic events possibly related to EGS have seriously affected/terminated some geothermal projects
- Implementation of safe stimulation strategies is critical for public acceptance of EGS projects

This study

- Near-realtime seismic monitoring allowed managing hydraulic energy input and avoid project-stopping M2.1 event during stimulation of a 6.1 km-deep geothermal well near Helsinki, Finland






St1 Deep Heat project


Located in Helsinki suburban area (Aalto University, Espoo)

Provide sustainable baseload for the campus-area district heating network



Project site

- Well OTN-3: **6.4 km MD**
- Open bottom-hole **1000 m** inclined at **45°**
- Target formations at **5.1-6.1 km** depth with bottom hole temperature **120°C**
- Simple geology
 - 10 m sedimentary overlay
 - precambrian granites, gneisses, amphibolites
- Complex small-scale tectonic structures (folded, foliated, jointed, faulted...)
 - Broad steeply dipping damage zones trending SE-NW (drilling problems)
 - FZ 8km away (M2.6), Inactive TF 1.5km away



OTN-3 stimulation campaign in June-July 2018

- **Five** stimulation stages selected using borehole logs

- Continuous stimulation of selected stages:

49 days

Water injected:

18,500 m³

Well head pressures:

60-90 MPa

Injection rates:

400-800 l/min



TLS RED M 2.1



Comparison:

Cooper Basin: **20,000 m³**

Basel: **11,500 m³**



Seismic activity during stimulation campaign

6,152 located in the vicinity of the project site
with magnitude estimate within 5 minutes after
occurrence ▶ TLS system

+10 minutes with manual refinement

St1: M^{\max} 1.9 @ 18,500m³ injected

No project-stopping red alert (M_{LHEL} 2.1)



Cooper Basin: M^{\max} 3.7 @ 20,000 m³

Basel: M^{\max} 3.4 @ 11,500 m³

Postprocessing:

Pick/amplitude pattern matching:


+40,000 events ($M_{\text{LHEL}} > -1.21$)

DD relocation: ~2000 events

(rel. precision 66-27m for 95%-68% of dataset)


Stimulation phase

- Phase 1
- Phase 2
- Phase 3
- Phase 4
- Phase 5





Seismicity during stimulation

- Three major clusters activated simultaneously
- No spatiotemporal correlation injection ports-seismicity ▶ leak bypassing stage packers near borehole
- Downward migration, propagation of seismicity along SE-NW subparallel to the direction of S_H^{MAX}





Controlling induced seismicity (Phase P1)

- Seismic activity occurs immediately after 75 MPa of WHP is exceeded ▶ no Kaiser effect
- Seismic energy release proportional to the hydraulic energy ($P \cdot V$)
- Quick reduction of seismic activity after injection subphases





Controlling induced seismicity (Phase P2)

- Change in injection strategy led to accelerated seismic moment release
- Series of large events forced premature finish of P2
- Stimulation stopped for a few days.





Controlling induced seismicity (Phase P2)

- Increase of M^{\max} with cumulative injected fluid volume. Trend following [Galis et al. \(2017\)](#).
 - ▶ $M^{\max, \text{arr}}$ depends on amount of stored elastic (\sim hydraulic) energy available for rupture propagation
 - ▶ Modified injection strategy: Reduce the amount of stored energy!




Controlling induced seismicity (Phase P3 P4 P5)

- P3: Reduction of WHP to < 90 MPa,
- P4-P5: Changing injection plan: up to 18 hrs injection / up to 12 hrs resting period, direct reaction on accelerating seismicity and occurrence of large events ▶ Stabilized injection efficiency





Successful control of M^{\max} likely due to:

- **Adaptive injection strategy** guided by real-time seismic monitoring - limiting **hydraulic energy input rate**.
- Possible **favorable stress conditions**, and **geological basement structures** of the reservoir
- *...Fortune favours the brave*





Re-activation of distributed fracture network (1)

- DD relocated data provides no evidence for alignment of seismicity along a large fault
- Damage zones visible in available engineering (log) and geological data
- Significant drop-off in the number of events above $M > 1.5$
 - No faults large enough to sustain larger events? Faults can't store enough elasting energy to support a runaway rupture?
- Seismic injection efficiency suggest reactivation of limited fracture network



Re-activation of distributed fracture network (2)



- Seismicity shows no evidence for alignment along a large fault
- Damage zones visible in available engineering and geological data
- Significant drop-off in the number of events above $M > 1.5$
 - No faults large enough to sustain larger events? Faults can't store enough elastic energy to support a runaway rupture?
- Seismic injection efficiency suggest reactivation of limited fracture network



GR distribution complexity testing following Lasocki and Papadimitriou, JGR, 2006

Low stress perturbation (1)

- Lower background tectonic stresses
- No pronounced clustering ▶ minor triggering? ▶ minor stress transfer?
- Relatively rapid dissipation of injected hydraulic energy
- Stationary b-value in later injection phases – no change in deviatoric stress ?
- Hazard seemingly controlled by GR a-value changes




Reshuffled catalog used to select separation level between clustered and background seismicity

Clustering procedure: [Baiesi and Paczuski, Phys. Rev. E, 2004](#); Separation clustered-background: [Davidsen et al., PRL, 2017](#)

Low stress perturbation (2)


- Lower background tectonic stresses than at other sites (Basel, Pohang)
- No pronounced clustering ▶ minor triggering? ▶ limited stress transfer?
- Relatively rapid dissipation of injected hydraulic energy
- Stationary b-value in later injection phases ▶ no change in deviatoric stress? (*Scholz, 1968*)
- Hazard seemingly controlled by GR a-value changes



b-value stationarity: ADF test (*Dickey and Fuller, J. Am. Stat. Assoc, 1979*)

Summary and conclusions

- Project stopping $M_{LHEL} 2.1$ earthquake was successfully avoided by adapting injection operations using near-realtime monitoring of induced earthquake rates, locations, magnitudes, and evolution of seismic and hydraulic energy
- Fluid injection was likely performed into a complex fracture/fault network leading to low stress perturbation. No major faults are known/were found in the reservoir
- Successful operation required close cooperation of seismologists, site operator, TLS team and local authorities during stimulation
- The outcome of the St1 DH project may indicate a possible approach allowing to manage induced seismicity in similar geothermal projects



Thank you very much for your attention!

Contact:

Grzegorz Kwiatek

kwiatek@gfz-potsdam.de

<https://induced.pl/about>

Stay tuned!

► *Kwiatek et al. (2019), Science Advances, in press*



ARUP



Keep calm
and drill.




Spare slides

Re-activation of distributed fracture network (3)

- Seismicity shows no evidence for alignment along a large fault
- Damage zones visible in available engineering and geological data
- Significant drop-off in the number of events above $M > 1.5$

No faults large enough to sustain larger events? Faults can't store enough elasting energy to support a runaway rupture?

- Seismic injection efficiency suggest reactivation of the fracture network



Bowland Shale: 10^{-1}
Horn River Basin 10^{-2}
Basel 7×10^{-3}
This study 3×10^{-3}
Aspo laboratory 10^{-5}
Horn River Basin 10^{-5}
Barnett: $10^{-9} - 10^{-7}$
Laboratory: $10^{-10} - 10^{-7}$

↑ Reactivation
Creation

Seismic injection efficiencies Goodfellow et al., GRL, 2015



Seismic monitoring networks

Stimulation

- 12 Shallow (0.3-1.3 km) borehole geophones
- 12 Deep (2.0-2.6 km) borehole sensors in OTN-2

TLS network

Surface 17 geophones






Stress magnitudes at the drill site were estimated from wellbore breakouts and minifrac shut-in pressures measured down to a depth of 1.8 km (13). Extrapolated to 6.1 km depth, these were estimated to be a $S_H^{\min}=110$ MPa, a $S_V=180$ MPa, and a $S_H^{\max}=240$ MPa. Pore pressures were assumed to be hydrostatic, equaling to approx. 60 MPa. Assuming a friction coefficient of 0.6, these results suggested that optimally oriented fractures and faults could be readily activated with moderate fluid pressure increases.

Data extension and refinement

Data reprocessing


- ▶ data refinement
- ▶ data reduction:
 - Full catalog including detections (~43,000 earthquakes above $M_{-1.21}$), sometimes constrained to $M_{-1.0}$ due to night-day cycle > **energy budget, b-value**
 - Relocated catalog using DD method (~1,950 earthquakes) with relative location precision ~60 m (95% confidence ellipse) > **spatio-temporal evolution, clustering**






Traffic Light System

- Thresholds based on PGV (critical facilities located nearby)
- All $M_{LHEL} > 1.2$ reported within 20 minutes to local authorities.
- $M_{LHEL} > 2.1$ Stop of the stimulation (...and waiting for approval from Finnish Authorities)




Mechanisms




Seismic center operation

- Performance for $M > 1.1$ without/with manual reprocessing: 5 / 15 minutes




Public response

- No complaints on ground motions during whole stimulation
- ... but nature likes to surprise us




Public response

- Over 60 complaints related to audible earthquake signals
- Remedy: Don't inject in the night



Detection limits

- Target: TLS (location+magnitude), tracking fracture network (optional)
- Outcome: EQs with $M > -0.3$ possible to locate, detection limit $M \cong -1.4$



Courtesy of fastloc GmbH